

■ Space111 LIGHTING EQUIPMENT					
Local Power Supply					
230 volt single phase, 60Hz					
Standard stage fixture connector ProPin Professional Stage Pin Connectors					
Control System					
Console	ION	2	ETC		
Networking	Net3 4-Port Gateway	1			
Backup System : ION Console With Switcher(Backup 4 Switch RS 4000N)					
Dimming System					
Dimmer	Sensor3	1 Set	ETC	5kW / 76 Dimmer (Dual Type)	
				5kW / 20 ThruPower (Dual Type)	
	1 Set	5kW / 48 Dimmer (Dual Type)			
	Sensor+	1 Set		5kW / 12 Dimmer (Dual Type)	
		1 Set		5kW / 24 Dimmer (Dual Type)	
Fixture					
E.R.S	25° ~ 50°	Source-Four Zoom / 750W	24	ETC	EDLT
	26°	Source-Four Standard / 750W	12		
	36°		24		
	50°		24		
	70°		6		
	90°		6		
Lens Tube	19°	For Source-Four Standard	6		EDLT
	70°		12		
	90°		12		
Fresnel		FQH - 650W S1	36	Marumo	With Barn door
		FQH - 1kW S1	18		
		MSM 805 - 1kW S1	12		
PAR64		1kW	50		
PAR46		250W	10 Sets		1 Set = 8EA / ACL
Flood		Lui / 1kW	8	Selecon	With Barn door
		Hui / 500W	10		
Zip Strip		ZS-3 / 1.5kW Per Circuit	4 Sets	Altman	1 Set = 2EA = 3 Circuit / ACL
Effect					
Fog Machine		UNIQUE 2	3	Look Solutions	
		Viper 2.6	1		
Effect Fan		JEM AF-1	2	Martin	
Film Machine		Film/FX	3	Gam	
Gobo Rotator		Smart Move	12	Apollo	With Power Supplies 4EA
Strobe		Atomic 3000 DMX	1	Martin	
Accessory					
Iris			15	Kupo	For Source-Four
Top Hat	Half	4 Inch	12		For Source-Four Standard
	Wide	4 Inch	12		
	Standard	4 Inch	36		
		6 Inch	12		For Source-Four Zoom
		8 Inch	18		For PAR64
T - Pipe		60cm(W)	30		
Stand	Long	2.5m	10		
	Middle	1m	10		
	Short	SHB-5 / 6cm	10	Marumo	
Side Arm		90cm	10	Altman	
		60cm	10		
Ladder		145cm(H) x 120cm(W)	4		
		80cm(H) x 120cm(W)	4		